
















## PVC Electrical Tapes

Product Name	Product Description	Thickness	Temperature Rating	Typical Applications	Typical Roll Size
 <p><b>Scotch™ Super 33+™ Professional Use Premium Vinyl Electrical Tape</b></p> 	Highly conformable, super stretchy in all weather applications. Resists UV rays, abrasion, corrosion, alkalis and acids. Flame retardant. Black. UL listed & CSA certified.	0.18mm (7mil)	105°C	Primary insulation for splices up to 600V. Protective jacketing.	<ul style="list-style-type: none"> <li>• 3/4" x 20' (19mm x 6.0m)</li> <li>• 3/4" x 44' (19mm x 13.4m)</li> <li>• 3/4" x 66' (19mm x 20.1m)</li> <li>• 1" x 36yd (25.4mm x 32.9m)</li> <li>• 1-1/2" x 36yd (38mm x 32.9m)</li> </ul>
 <p><b>Scotch™ Professional Use Vinyl Electrical Tape 35</b></p> <p>Colors available:</p>  	Fade-resistant colors, super stretchy and conformable, excellent insulating properties. Resists UV rays, abrasion, corrosion, alkalis and acid. Flame retardant. UL listed & CSA certified.	0.18mm (7mil)	105°C	Phase identification and marking. Harnessing. Insulates splices up to 600V.	<ul style="list-style-type: none"> <li>• 3/4" x 60' (19mm x 18.2m)</li> <li>• 3/4" x 66' (19mm x 20.1m)</li> <li>• 1/2" x 20' (12mm x 6.1m)</li> </ul>
 <p><b>Scotch™ Professional Use Premium Vinyl Electrical Tape Super 88</b></p> 	Thick, heavy duty all weather vinyl, abrasion resistant, fast buildup. Resists UV rays, corrosion, alkalis and acids. Flame retardant. Black. UL listed & CSA certified.	0.22mm (8.5mil)	105°C	Primary insulation for splices up to 600V. Protective jacketing.	<ul style="list-style-type: none"> <li>• 3/4" x 44' (19mm x 13.4m)</li> <li>• 3/4" x 66' (19mm x 20.1m)</li> <li>• 1" x 36yd (25.4mm x 32.9m)</li> <li>• 1-1/2" x 44' (38mm x 13.4m)</li> </ul>
 <p><b>Scotch™ Heavy Duty Vinyl Electrical Tape 22</b></p> 	Extra thick for increased mechanical strength, abrasion resistance and faster buildup. Electrical insulating. Resists UV rays, corrosion, alkalis and acids. Flame retardant. Black. UL listed & CSA certified.	0.25mm (10mil)	80°C	Bus bar insulation. Cable jacket repair.	<ul style="list-style-type: none"> <li>• 1/2" x 36yd (13mm x 32.9m)</li> <li>• 3/4" x 36yd (19mm x 32.9m)</li> <li>• 1" x 36yd (25.4 mm x 32.9m)</li> <li>• 1-1/2" x 36yd (38mm x 32.9m)</li> </ul>
 <p><b>Temflex™ Vinyl Electrical Tape 1710</b></p> <p>Colors available:</p>  	Flexible. General purpose tape with good cool temperature adhesion. Flame retardant. UL listed & CSA certified.	0.18mm (7mil)	80°C	Primary insulation up to 600V. Protective jacketing. Wire harnessing and bundling. Phase identification and marking.	<ul style="list-style-type: none"> <li>• 3/4" x 11yd (18mm x 10m)</li> </ul>
 <p><b>Temflex™ Vinyl Electrical Tape 1500</b></p> <p>Colors available:</p> 	Economical. Flexible. General purpose tape in a range of colors.	0.13mm (5mil)	80°C	Primary insulation up to 600V. Protective jacketing. Wire harnessing and bundling. Phase identification and marking.	<ul style="list-style-type: none"> <li>• 3/4" x 5.5yd (18mm x 5m)</li> </ul>
 <p><b>Temflex™ GU Vinyl Electrical Tape</b></p> <p>Colors available:</p> 	Economical. General purpose tape in a range of colors.	0.12mm (4.7 mil)	80°C	Primary insulation up to 600V. Protective jacketing. Wire harnessing and bundling. Phase identification and marking.	<ul style="list-style-type: none"> <li>• 3/4" x 5.5yd (18mm x 5m)</li> </ul>



Flame retardant.



are registered trademarks of Underwriters Laboratories, Incorporated.



is a registered trademark of Canadian Standards Association.