



- Display : 4000 counts.
- Auto range and manual range selector provided. (with range hold feature)
- Resistance range provides audible continuity test.
- Automatically turns power off in about 30 minutes to conserve battery life.
- Direct current measurement up to 10A AC and DC.
- With Holster.

CE



DC V	400mV/4/40/400/600V (Input Impedance 10MΩ) ±0.6%rdg±4dgt (400mV/4/40/400V) ±1.0%rdg±4dgt (600V)
AC V	400mV/4/40/400/600V (Input Impedance 10MΩ) ±1.6%rdg±4dgt (20 - 400mV) ±1.3%rdg±4dgt (4/40V) ±1.6%rdg±4dgt (400/600V)
DC A	400/4000μA/40/400mA/4/10A ±2.0%rdg±4dgt (400/4000μA)±1.0%rdg±4dgt (40/400mA) ±1.6%rdg±4dgt (4/10A)
AC A	400/4000μA/40/400mA/4/10A ±2.6%rdg±4dgt (400/4000μA) ±2.0%rdg±4dgt (40/400mA/4/10A)
Ω	400Ω/4/40/400kΩ/4/40MΩ ±1.0%rdg±4dgt (400Ω/4/40/400kΩ/4MΩ) ±2.0%rdg±4dgt (40MΩ)
Continuity buzzer	400Ω (Buzzer sounds below 100Ω)
Diode test	1.5V Release Voltage:Approx. 0.4mA Test Current
Capacitance	40/400nF/4/40/100μF
Frequency	5.12/51.2/512Hz/5.12/51.2/512kHz/5.12/10MHz
DUTY	0.1 - 99.9% (Pulse width/Pulse period) ±2.5%±5dgt
Applicable standards	IEC 61010-1 CAT III 300V IEC 61010-2-031 IEC 61326
Power source	R6 (1.5V) × 2
Dimensions	161(L) × 82(W) × 50(D)mm
Weight	Approx. 280g
Included Accessories	7066A (Test leads) 8919 (Ceramic fuse [10A/600V])× 1 8923 (Fuse [0.5A/600V])× 1 R6× 2 Instruction Manual
Optional Accessories	7234 (Crocodile clip test lead) 9095 (Carrying case)