

# SEPARABLE INSULATING TERMINAL BLOCKS

## Without fastening tab

Code	Reference	Cross-section 2 cables of :	Terminals per strip	Pack
01001	70006	6 mm <sup>2</sup>	10	200 Terminals
01002	70010	10 mm <sup>2</sup>	8	80 Terminals
01003	70016	16 mm <sup>2</sup>	8	80 Terminals
01004	70025	25 mm <sup>2</sup>	8	80 Terminals
01005	70035	35 mm <sup>2</sup>	6	60 Terminals
01006	70070	70 mm <sup>2</sup>	4	40 Terminals
01007	70120*	120 mm <sup>2</sup>	4	20 Terminals



Ref. 70035

## With fastening tab

Code	Reference	Cross-section 2 cables of :	Terminals per strip	Pack
01101	7006	6 mm <sup>2</sup>	10	200 Terminals
01102	7010	10 mm <sup>2</sup>	8	80 Terminals
01103	7016	16 mm <sup>2</sup>	8	80 Terminals
01104	7025	25 mm <sup>2</sup>	8	80 Terminals
01105	7035	35 mm <sup>2</sup>	6	60 Terminals
01106	7070	70 mm <sup>2</sup>	4	40 Terminals
01107	7120*	120 mm <sup>2</sup>	4	20 Terminals



Ref. 7016

\* Nota : 120 mm<sup>2</sup> terminals secured with 8 mm hex spanner (1 spanner per pack).

Certificated of compliance  and 

	Cat Number	AWG (CU)	Voltage (V)	Amps (A)	Torque (kg-m)
CSA NRTL/C	7006 : 70006	16	600	13	0.10
	7010 : 70010	10	600	30	0.18
	7016 : 70016	6	600	50	0.20
	7025 : 70025	1	600	50	0.20
	7035 : 70035	2/0	600	100	0.35
	7070 : 70070	2/0	600	150	0.60
	7120 : 70120	4/0	600	200	2.50


# SHUNT TERMINAL

This connector enables you to connect two or more conductors without the cable, simply remove a section of the cable insulation and place in the slot. Replace the top section and repeat with the second cable.

Other features include :

- The conducting parts are made of plated brass, the insulated parts are Urea Formaldehyde
- The top of secondary circuit is above the main conductor
- Captive screws on the top
- Conductor clamping screws are socket grub screws which ensure firm clamping
- One cable can be copper and the other aluminium
- Cable can enter through the base

Code	Reference	Cross section	Outside dimensions	Screws	Pack	Weight (g)
01120	B0105002	50 mm <sup>2</sup>	46 x 46,5 x 64	3	15	145
01125	B0109000	95 mm <sup>2</sup>	74 x 68 x 79	5	9	390
01130	B0115001	150 mm <sup>2</sup>	74 x 68 x 103	5	10	555
01135	B0124003	240 mm <sup>2</sup>	105 x 92 x 111	6	6	1125
01140	B0130004	300 mm <sup>2</sup>	105 x 92 x 136	8	6	1425



Ref. B0124003