

HYDRAULIC CRIMPING TOOLS

TOPT-TP-325 Hydraulic Crimping Tool (Pre-order)

A hydraulic crimping tool for Copper cable lugs and connectors.

Crimping Type	: Indent
Crimping Range	: 16mm ² to 400mm ²
Output force	: 18 Tons
Weight / Length	: 6.2kgs / 650mm (Tool only)

Set includes	: Crimping Tool and 4pcs of Male dies (16, 25-35, 50-120, 150-400mm ²) 8pcs Female Dies (16-25, 35-70, 95-120, 150, 185, 240, 300 & 400mm ²) Carrying case
--------------	--



TOPT-TP-420H Hydraulic Crimping Head (Pre-order)

A hydraulic crimping head for Copper cable lugs and connectors.

Crimping Type	: Hexagon
Crimping Range	: 35mm ² to 400mm ²
Jaw Opening	: 42mm C-Jaw
Output force	: 12 Tons
Weight / Length	: 5.3kgs / 250mm (Head only)

Set includes	: Crimping Tool and 10pcs of dies set (35, 50, 70, 95, 120, 150, 185, 240, 300 & 400mm ²) Carrying case
--------------	---



PNEUMATIC CRIMPING MACHINES

TOPT-PA-6B Pneumatic Drived Crimping Head with PF-1 Foot Pedal

A Pneumatic type crimping tool for connectors.

Output force : 1.3 tons output at air pressure 5 bars

Weight / Length : 2.7 kg / 225 (L) x 90 (W) x 135 (H) mm (excludes PF-1)

Notes :

1. Extra Crimping dies can be purchased separately.
2. The dies are also compatible with LY-03C/LY-03B/LY-16WF.
3. Crimping head needs to work with an air compressor.



HYDRAULIC CABLE CUTTER

TOPT-CPC-85A Hydraulic Cable Cutter (Pre-order)

Applications	: Cutting of Copper & Aluminium PVC Cable
Output Force	: 5 Tons
Cutting Range	: Bare Copper Wire Strand Max. O.D. 28 mm Bare Aluminium Wire Strand Max. O.D. 38 mm CCP Cable Max. O.D. 85 mm Underground Cable Max O.D. 50 mm
Total Length	: 695mm
Weight	: 7kgs
Remark	: Free Pin Design
Note	: DO NOT use it to cut any rebar, steel wire or armoured cables.



TOPT-HT-85 Hydraulic Cable Cutter Head

Applications	: Cutting of Copper & Aluminium PVC Cable
Input Pressure	: Max. 700bar or 10,000psi
Opening Jaw	: 85mm
Cutting Range	: Up to 85mm OD (for Telephone Cu/Al Cable) Up to 50mm OD (for Underground Cable)
Length	: 456mm
Weight	: 6kgs
Note	: DO NOT use it to cut any rebar, steel wire or armoured cables.



TOPT-S-100H Hydraulic Cable Cutter Head

Applications	: Cutting of Copper & Aluminium Cable including Armoured Cable
Input Pressure	: Max. 700bar or 10,000psi
Opening Jaw	: 100mm
Cutting Range	: Up to 100mm OD
Total Length	: 570mm
Weight	: 14kgs



Notes:

1. S-100H & HT-85 cutters can be paired with CONWAY range of Electric and Hydraulic pumps:
 - TCPM-1000
 - TCCP-630HP
 - TCCP-630FP
 - TOPT-F-B

CORDLESS CRIMPING TOOL

12 Tons Cordless Crimping Tools (18V) (Pre-order)

3 sizes C-head opening. 360 degrees swivel head.

Pistol type crimper. Cable Lug hexagon crimping.

Standard die set (total 10pcs). 35/50/70/95/120/150/185/240/300/400mm²

EPB-4301

43mm C-jaw opening

Insulated fixed knob

35-400mm² crimping Range

Tool Dimension: 440(L) x 290(W) x 78(H)mm

Weight: 6.8kgs excludes battery

Includes:



CH-07C
(18V Li-Ion Charger)
1 unit



B-05C
(18V Li-Ion Battery 5Ah)
2 units



EPB-4301

18 Tons Cordless Crimping Tools (18V) (Pre-order)

360 degrees swivel head.

Pistol type crimper.

Cable Lug hexagon crimping.

Standard die set (total 12pcs) 35/50/70/95/120/150/185/240/300/400/500/630mm²

Below 400mm² required to use AR-630 adaptor.

EPB-6301 (18V Li-Ion)

35-630mm² crimping range

Tool Dimension: 420(L) x 330(W) x 90(H)mm

Weight: 7.4kgs excludes battery

Includes:



CH-07C
(18V Li-Ion Charger)
1 unit



B-05C
(18V Li-Ion Battery 5Ah)
2 units



EPB-6301

6 Tons Cordless Crimping Tools (Pre-order)

180 degrees swivel head.

Inline type crimper/Flip-open jaw type.

17mm stroke / 3-6 seconds pressure time.

Cable lug hexagon crimping.

Standard die set (total 7pcs).

70/95/120/150/185/240/300mm²

MEPB-22 (18V Li-Ion)

70-300mm² crimping range

Tool dimension: 380(L) x 122 (W) x 76(H)mm

Weight: 3.1kgs excludes battery

Includes:



CH-07C
(18V Li-Ion Charger)
1 unit



B-05C
(18V Li-Ion Battery 5Ah)
2 units



MEPB-22

60 TONS REMOTE HYDRAULIC CRIMPING HEAD

TOPT-OP-60D (Pre-order)

Double Acting Hydraulic Crimping Head.
For distribution, transmission line and sleeve, lug crimping.
Remote Control type, needs to work with TCPM-3001 Electric Pump.

Crimping Type	: Hexagon
Crimping Range	: For connector or lug up to O.D. 60mm
Output force	: 60 Tons output/ 38mm stroke
Oil Volume	: 308c.c.
Weight / Length	: 28kgs / 146x450mm (Head Only)



TOPT-OP-60D-BOX
Outer & Inner

Notes :

1. Dies are sold separately.
2. Only can be paired with Electric Pump. (TCPM-3001).

CORDLESS CABLE CUTTER

12 Tons Cordless Cable Cutters (Pre-order)

For copper, aluminum cable, lead-sheathed cable,
armoured underground cable cutting 360-degree swivel head.
For copper & aluminum cable Max. O.D. 65mm
For lead-sheathed cable Max. O.D. 65mm
For armored underground cable Max. O.D. 65mm



Includes:



CH-07C
(18V Li-Ion Charger)
1 unit



B-05C
(18V Li-Ion Battery 5Ah)
2 units

ECB-65Y (18V Li-Ion)

Tool Dimension: 555(L) x 370(W) x 240(H)mm
Weight: 11.3kgs excludes Battery

Mechanism Cordless Cutters (Pre-order)

Super-durable type
Copper & Aluminium cable: DIN cable Max. 1000mm² (2000MCM)
Max. Blade opening: 65mm



Includes:



CH-07C
(18V Li-Ion Charger)
1 unit



B-05C
(18V Li-Ion Battery 5Ah)
2 units

ECB-67 (18V Li-Ion)

Tool Dimension: 175(L) x 110(W) x 320(H)mm
Weight: 2.8kgs excludes Battery

6 Tons Cordless Cable Cutters (Pre-order)

360 degrees swivel head
Pistol type cutters
Wire rope (hemp-core) 6x12/6x19 Max. O.D. 25mm
Soft copper & aluminum round bar Max. O.D. 20mm
Bare copper & aluminum wire strand Max. O.D. 32mm
Armored underground cable Max. O.D. 45mm
Soft steel round bar (Below SS41) Max. O.D. 16mm
Wire rope (hemp-core) 6x7 Max. O.D. 20mm



Includes:



CH-07C
(18V Li-Ion Charger)
1 unit



B-05C
(18V Li-Ion Battery 5Ah)
2 units

ECB-45 (18V Li-Ion)

Tool dimension: 440(L) x 315(W) x 75(H)mm
Weight: 5.8kgs excludes Battery